

Number of CB4856-markers	75
RTI-specific N2/CB4856 ratio	0.613

KDE Specific N2/CD4650 Ratio 0.015 1.405 1.951 0.592 0.691 1.066 0.30 0.030 1.241 1.574 2.457 1.066 0.055 2.104 1.05 1.551 2.27 0.458 4.5 1.2 0.552 0.450 0.552 0.552

0.613 1.283 1.951 0.107 1.2 2.184 0.592 0.952 0.833 1.051 1.051 1.327 0.476 0.891 0.862 3.654 0.391 0.891 1.123 0.729 1.017 1.123 3.654 2.27 1.469 3.033 1.2 0.779 1.814

marker segregation ratio N2/CB4856
1.9630
2.0769
8.8750
10.2857
5.0769
3.0000
3.2105
3.3889
3.2105
3.1579
3.2105
3.0000
2.4783
2.4783
2.2917
2.1600
2.0769
1.7586
1.6667
1.6667
0.8372
0.8372
0.8372
0.7391
0.7021
0.6809
0.7556
0.6809
0.6809
0.7174
0.7174
0.7556
0.7556
0.7556
0.7174
0.7556
0.7955
0.8372
1.1053
1.1944
0.9750
0.9750
1.0789
1.3235
1.2571
1.3939
1.3235
1.0789
1.0789
1.0256
1.0256
1.0789
1.0256
1.0256
1.0256
1.0256
1.0256
1.3235
1.4688
1.2571
1.3235
1.1944
0.8372
0.8372
0.8372
0.7556
0.7556
0.8372
0.8372
0.7556
0.7174
0.7174
0.7174
0.7174
0.6458
0.6809
0.7174
0.6458
0.7174
0.7174
1.0789
0.9750
0.9268
0.8372
0.7556
0.7556
0.8372
0.7174
0.7174
0.6809
0.7174
0.7556
0.7556
0.7955
0.8810
0.8372
0.8372
0.6458
0.7174
0.8372
0.8372
1.6333
1.7241
1.6333
1.8214
1.7241
1.8214
1.9259
1.4688
1.7241
1.7241
1.5484
1.6333
1.3235
1.2571
1.3235
1.0789
1.3235
1.1944
1.1944
1.1944