Closed Form Solutions for Unsteady Free Convection Flow of a Second Grade Fluid over an Oscillating Vertical Plate

Farhad Ali¹, Ilyas Khan^{1,2}, Sharidan Shafie^{1*}

1 Department of Mathematical Sciences, Faculty of Science, Universiti Teknologi Malaysia, Johor Bahru Johor, Malaysia, **2** College of Engineering Majmaah University, Majmaah, Kingdom of Saudi Arabia

Abstract

Closed form solutions for unsteady free convection flows of a second grade fluid near an isothermal vertical plate oscillating in its plane using the Laplace transform technique are established. Expressions for velocity and temperature are obtained and displayed graphically for different values of Prandtl number Pr , thermal Grashof number Gr , viscoelastic parameter α , phase angle $\omega\tau$ and time τ . Numerical values of skin friction τ_0 and Nusselt number Nu are shown in tables. Some well-known solutions in literature are reduced as the limiting cases of the present solutions.

Citation: Ali F, Khan I, Shafie S (2014) Closed Form Solutions for Unsteady Free Convection Flow of a Second Grade Fluid over an Oscillating Vertical Plate. PLoS ONE 9(2): e85099. doi:10.1371/journal.pone.0085099

Editor: Enrique Hernandez-Lemus, National Institute of Genomic Medicine, Mexico

Received: July 29, 2013; **Accepted:** November 22, 2013; **Published:** February 14, 2014

Copyright: © 2014 Ali et al. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Funding: These authors have no support or funding to report.

Competing Interests: The authors have declared that no competing interests exist.

* E-mail: ridafie@yahoo.com

Introduction

It is well known that Newtonian fluids such as air, water, ethanol, benzene and mineral oils form a basis for classical fluid mechanics. However, many important fluids, such as blood, polymers, paint, and foods show non-Newtonian behavior. Due to the diversity of non-Newtonian fluids in nature no unique relationship is available in the literature that can describe the rheology of all the non-Newtonian fluids. Of course, the mathematical systems for non-Newtonian fluids are of higher order and complicated in comparison to the Newtonian fluids. Therefore, a variety of constitutive equations have been suggested to predict the behavior of non-Newtonian fluids. Despite of all these difficulties, the recent researchers in the field have made valuable contributions in study of flows of non-Newtonian fluids [1–12]. Amongst the different categorizations of non-Newtonian fluids, there is one simplest model of differential type fluids known as second grade fluid [13,14]. Keeping the importance of non-Newtonian fluids in mind, for the present problem, we have chosen second grade fluid as a non-Newtonian fluid. Amongst the different studies on second grade fluids [15–25], Nazar et al. [26] provided some interesting results. They considered the second grade fluid over an oscillating plate and obtained exact solutions using the Laplace transform technique, expressed them as the sum of steady-state and transient solutions. Recently, Farhad et al. [27] extended the work of Nazar et al. [26] by considering the second grade fluid to be electrically conducting and passes through a porous medium. As a special case, it is observed that their results in the absence of MHD and porosity effects are reduced to those obtained by Nazar et al. [26].

On the other hand free convection is a common process in nature and has numerous applications and occurrences in industry. It is a major cause of atmospheric and oceanic circulation

and plays an important role in the passive emergency cooling systems of advanced nuclear reactors. Furthermore, free convection flows of non-Newtonian fluids with heat transfer play an important role in many industrial systems. For example, there are many process in which thermal energy is transferred from an object through the physical contact with heat transfer fluids at a temperature colder than the object. Industrial refrigeration or heating, chemical manufacturing, breweries, ventilation and air conditioning, ice rinks and engine cooling, environmental chambers, oil and gas industry and, food and pharmaceutical are some examples of such applications [28–30]. Besides that, the Stokes' second problem for the flow of an incompressible fluid over an oscillating plane is of great importance in the literature of fluid dynamics. It admits an exact analytical solution [31]. The Stokes' or Rayleigh problem is not only of fundamental theoretical interest but it also occurs in many applied problems [32,33].

Pop and Watanabe [34] investigated the effects of suction and injection on the free convection flow from vertical cone with uniform surface heat flux with fixed value of $Pr = 0.7$ and obtained numerical solutions. Kafoussias [35] studied free convection magnetohydrodynamic flows through porous medium and obtained numerical solutions for constant viscosity. In the investigations [34,35], the coefficients of viscosity are assumed constant. However, it is observed the coefficients of viscosity for most fluids may depend on temperature [36]. Many investigations have been reported into the problem of free convection heat transfer along a vertical surface with temperature dependent viscosity for different heating conditions [37–41]. Jang and Lin [42] studied the role of temperature-dependent viscosity in laminar free convection flow adjacent to a vertical surface with uniform heat flux.

Most of the existing studies in the literature on convection flows of second grade fluid are concerned with numerical or approximate solutions [43–45]. Considerably less work has been reported

concerning the constant property effects on free convection flow of second grade fluid over the vertical isothermal plate. So, it is necessary to carry out the study on free convection flows of second grade fluid with exact solutions for the free convection flow of second grade. Exact solutions on the other hand are needed not only for the technical relevance of the flows but are also significant for a variety of other reasons such as they can be used as a benchmark by numerical solvers and for checking the stability of their solutions. Therefore, the main purpose of the present investigation is to study the unsteady free convection flow of a second grade fluid past an isothermal vertical plate oscillating in its plane with constant viscosity [34,35], and to obtain the exact solutions using the Laplace transform technique. The present problem is the extension of Nazar et al. [26]. However, it is rather complicated due to the presence of free convection term in the momentum equation which makes the momentum and energy equations coupled with each others. Hence the present solutions are more general compared to the solutions existing in the literature.

Formulation of the Problem

Following Fosdick and Rajagopal [13], the Cauchy stress tensor $\mathbf{T}$ in a homogeneous incompressible fluid of second grade is related to the fluid motion in the following form

$$\mathbf{T} = -p\mathbf{I} + \mu\mathbf{A}_1 + \alpha_1\mathbf{A}_2 + \alpha_2\mathbf{A}_1^2, \quad (1)$$

where p is the scalar pressure, $\mathbf{I}$ is the identity tensor, μ is the coefficient of viscosity, α_1 and α_2 are the material moduli

commonly referred to as the normal stress moduli and $\mathbf{A}_1$ and $\mathbf{A}_2$ stand for the first two tensor of Rivlin and Ericksen defined by

$$\mathbf{A}_1 = \mathbf{L} + \mathbf{L}^T, \quad \mathbf{A}_2 = \frac{d\mathbf{A}_1}{dt} + \mathbf{A}_1\mathbf{L} + \mathbf{L}^T\mathbf{A}_1. \quad (2)$$

According to Fosdick and Rajagopal [13] and Dunn and Fosdick [14] the model (1) required to be compatible with thermodynamics in the sense that all motions satisfy the Clausius-Duhem inequality and the assumption that the specific Helmholtz free energy is a minimum in equilibrium at constant temperature then, the material moduli must satisfy the following conditions

$$\mu \geq 0, \quad \alpha_1 \geq 0, \quad \alpha_1 + \alpha_2 = 0. \quad (3)$$

Now let us consider the unsteady free convection flow of a second grade fluid near an isothermal vertical plate situated in the (x, z) plane of a Cartesian coordinate system x, y and z . Initially, both the plate and fluid are at rest with constant temperature T_∞ . At time $t=0^+$, the plate starts motion in its plane with oscillating velocity and then transmitted to the fluid. The temperature of the plate immediately raises to T_w and thereafter maintains constant. Owing to the shear, the fluid is gradually moved and its velocity is of the form

$$\mathbf{v} = v(y; t) = u(y, t)\mathbf{i}; \quad (4)$$

where $\mathbf{i}$ is the unit vector in the flow direction as shown in Fig. 1.

In the view of the above assumptions and using the usual Boussinesq approximation, the momentum and energy equations for the incompressible flow of a second grade fluid are

Figure 1. Physical geometry and coordinates system.

doi:10.1371/journal.pone.0085099.g001

$$\rho \frac{\partial u}{\partial t} = \mu \frac{\partial^2 u}{\partial y^2} + \alpha_1 \frac{\partial^3 u}{\partial y^2 \partial t} + g\beta_T(T - T_w), \quad (5)$$

$$\rho c_p \frac{\partial T}{\partial t} = k \frac{\partial^2 T}{\partial y^2}. \quad (6)$$

The appropriate initial and boundary conditions

$$u(y, 0) = 0, \quad T(y, 0) = T_\infty, \quad y > 0,$$

$$u(0, t) = UH(t) \cos(\omega_1 t) \quad \text{or} \quad u(0, t) = U \sin(\omega_1 t), \quad t > 0,$$

$$T(0, t) = T_w, \quad t > 0,$$

$$u(\infty, t) = 0, \quad T(\infty, t) = T_\infty, \quad t > 0, \quad (7)$$

where $u = u(y, t)$ denotes the fluid velocity in the x -direction, $T = T(y, t)$ is the temperature, ρ is the constant density of the fluid, μ is the viscosity, α_1 is the second grade parameter, β_T is the volumetric coefficient of thermal expansion, g is the acceleration due to gravity, c_p is the specific heat capacity, k is the thermal conductivity, T_∞ is the free stream temperature, ω_1 the frequency of the velocity of the wall and $H(t)$ is the Heaviside unit step function.

By introducing the following dimensionless variables

$$v = \frac{u}{U}, \quad \xi = \frac{U}{\nu} y, \quad \tau = \frac{U^2}{\nu} t, \quad \omega = \frac{\nu}{U^2} \omega_1, \quad \theta = \frac{T - T_\infty}{T_w - T_\infty}, \quad (8)$$

the system of equations (5)–(7) reduces to

$$\frac{\partial v}{\partial \tau} - \frac{\partial^2 v}{\partial \xi^2} - \alpha \frac{\partial^3 v}{\partial \xi^2 \partial \tau} - Gr\theta = 0, \quad (9)$$

$$Pr \frac{\partial \theta}{\partial \tau} = \frac{\partial^2 \theta}{\partial \xi^2}, \quad (10)$$

$$v(\xi, \tau) = 0; \quad \theta(\xi, \tau) = 0; \quad \tau \leq 0,$$

$$v(0, \tau) = H(\tau) \cos(\omega \tau) \quad \text{or}$$

$$v(0, \tau) = \sin(\omega \tau), \quad \theta(0, \tau) = 1 \quad \tau > 0,$$

$$v(\infty, \tau) = 0, \quad \theta(\infty, \tau) = 0, \quad \tau > 0, \quad (11)$$

where

$$\alpha = \frac{\alpha_1 U^2}{\rho \nu^2}, \quad Gr = \frac{g \beta_T \nu (T_w - T_\infty)}{U^3}, \quad Pr = \frac{\mu c_p}{k}.$$

Here α is the dimensionless second grade parameter, Gr is the thermal Grashof number and Pr is the Prandtl number.

Solution of the Problem

We solve the governing equations in exact form by the Laplace transform technique and their solutions in the transform (y, q) -plane are given by

$$\bar{v}_c(\xi, q) = \frac{q}{q^2 + \omega^2} \exp\left(-\frac{\xi}{\sqrt{\alpha}} \sqrt{\frac{q}{q + \beta}}\right) + \frac{a}{q^2(q - b)} \exp\left(-\frac{\xi}{\sqrt{\alpha}} \sqrt{\frac{q}{q + \beta}}\right)$$

$$- \frac{a}{q^2(q - b)} \exp\left(-\xi \sqrt{Pr q}\right), \quad (12)$$

$$\begin{aligned} \bar{v}_s(\xi, q) &= \frac{\omega}{q^2 + \omega^2} \exp\left(-\frac{\xi}{\sqrt{\alpha}} \sqrt{\frac{q}{q + \beta}}\right) \\ &+ \frac{a}{q^2(q - b)} \exp\left(-\frac{\xi}{\sqrt{\alpha}} \sqrt{\frac{q}{q + \beta}}\right) \\ &- \frac{a}{q^2(q - b)} \exp\left(-\xi \sqrt{Pr q}\right), \end{aligned} \quad (13)$$

$$\bar{\theta}(\xi, q) = \frac{1}{q} \exp\left(-\xi \sqrt{Pr q}\right), \quad (14)$$

where the subscripts c and s in Eqs. (12) and (13) refer to cosine and sine oscillations of the plate and

$$a = \frac{Gr}{\alpha Pr}, \quad \beta = \frac{1}{\alpha}, \quad b = \frac{1 - Pr}{\alpha Pr}, \quad Pr \neq 1.$$

We split Eq. (12) in the following forms

$$\bar{v}_1(q) = \frac{q}{q^2 + \omega^2}, \quad \bar{v}_4(\xi, q) = \frac{a}{q^2(q - b)} \exp\left(-\xi \sqrt{Pr q}\right), \quad (15)$$

$$\bar{v}_2(q) = \frac{a}{q^2(q - b)},$$

$$\bar{v}_3(\xi, q) = \exp\left(-\frac{\xi}{\sqrt{\alpha}} \sqrt{\frac{q}{q + \beta}}\right). \quad (16)$$

Let us we denote

$$v_1(\tau) = \mathcal{L}^{-1}\{\bar{v}_1(q)\}, \quad v_2(\tau) = \mathcal{L}^{-1}\{\bar{v}_2(q)\},$$

$$v_3(\xi, \tau) = \mathcal{L}^{-1}\{\bar{v}_3(\xi, q)\}, \quad v_4(\xi, \tau) = \mathcal{L}^{-1}\{\bar{v}_4(\xi, q)\},$$

where $\mathcal{L}^{-1}$ is denoting the inverse Laplace transform.

In order to find the inverse Laplace transform of Eq. (12), we write the velocity $v_c(\xi, \tau)$ as a convolution product (see theorem (A1) from Appendix S1).

$$v_c(\xi, \tau) = \int_0^\tau v_1(\tau - s) v_3(\xi, s) ds + \int_0^\tau v_2(\tau - s) v_3(\xi, s) ds - v_4(\xi, \tau). \quad (17)$$

Laplace inversion of Eq. (15) leads to the following expressions.

$$v_1(\tau) = \cos(\omega \tau), \quad v_2(\tau) = \frac{a(e^{b\tau} - b\tau - 1)}{b^2}, \quad (18)$$

$$\begin{aligned} v_4(\xi, \tau) &= \frac{ae^{b\tau}}{2b^2} \\ &\left[e^{-\xi \sqrt{b Pr}} \operatorname{erf} c \left(\frac{\xi \sqrt{Pr}}{2\sqrt{\tau}} - \sqrt{b\tau} \right) + e^{\xi \sqrt{b Pr}} \operatorname{erf} c \left(\frac{\xi \sqrt{Pr}}{2\sqrt{\tau}} + \sqrt{b\tau} \right) \right] \\ &- \frac{a}{b} \left[\left(\tau + \frac{\xi^2 Pr}{2} \right) \operatorname{erf} c \left(\frac{\xi \sqrt{Pr}}{2\sqrt{\tau}} \right) - \frac{\xi \sqrt{Pr} \tau}{\sqrt{\pi}} e^{-\frac{\xi^2 Pr}{4\tau}} \right] \\ &- \frac{a}{b^2} \operatorname{erf} c \left(\frac{\xi \sqrt{Pr}}{2\sqrt{\tau}} \right). \end{aligned} \quad (19)$$

In order to find $v_3(\xi, \tau)$, we use the inversion formula of compound functions (A2) and some of the known results (A4)-(A7) from Appendix S1, consequently Eq. (16) results.

$$v_3(\xi, \tau) = \frac{\xi \delta(\tau)}{2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{\xi e^{-\beta\tau}\sqrt{\beta}}{2\sqrt{\alpha\pi\tau}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u} I_1(2\sqrt{\beta u\tau}) du, \quad (20)$$

where $\delta(\cdot)$ is the Dirac delta function and $I_1(\cdot)$ is the modified Bessel function of the first kind of order one. Using Eqs. (18)-(20) into Eq. (17), keeping in mind (A3) from Appendix S1, we get

The starting solutions of $v_c(\xi, \tau)$ and $v_s(\xi, \tau)$ given by Eqs. (21) and (22) are rather complicated. Therefore, we derive approximate expressions for these velocities corresponding to small and large values of time. This time is important, especially for those who need to eliminate transients from their rheological measurements [26]. In order to determine this time, we need first to write the starting solutions as the sum of the steady state and transient solutions. Therefore, we decompose the integrals from Eqs. (21) and (22) under the form

$$\int_\tau^\infty f(\xi, \tau, s) ds = \int_0^\infty f(\xi, \tau, s) ds - \int_\tau^\infty f(\xi, \tau, s) ds \quad (23)$$

and use formulae (A8)-(A10) from Appendix S1, we obtain

$$\begin{aligned} v_c(\xi, \tau) = & \frac{\xi H(\tau) \cos(\omega\tau)}{2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{\xi H(\tau)\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} \\ & I_1(2\sqrt{\beta us}) du ds + \frac{a\xi(e^{b\tau} - b\tau - 1)}{2b^2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du \\ & + \frac{a\xi\sqrt{\beta}e^{b\tau}}{2b^2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\left[\exp\left(-\frac{\xi^2}{4zu} - u - \beta s - bs\right) - b(\tau - s) - 1\right]}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\ & - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\text{Pr}}} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{b\text{Pr}}} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] \\ & + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \text{Pr}}{2}\right) \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\text{Pr}}\tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \text{Pr}}{4\tau}} \right] + \frac{a}{b^2} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}}\right). \end{aligned} \quad (21)$$

Similarly for the sine oscillations of the plate the corresponding expression of velocity is given by

$$v_c(\xi, \tau) = v_{cs}(\xi, \tau) + v_{ct}(\xi, \tau), \quad v_s(\xi, \tau) = v_{ss}(\xi, \tau) + v_{st}(\xi, \tau), \quad (24)$$

where the steady state solutions are written as

$$\begin{aligned} v_s(\xi, \tau) = & \frac{\xi \sin(\omega\tau)}{2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\ & + \frac{a\xi(e^{b\tau} - b\tau - 1)}{2b^2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{a\xi\sqrt{\beta}e^{b\tau}}{2b^2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\left[\exp\left(-\frac{\xi^2}{4zu} - u - \beta s - bs\right) - b(\tau - s) - 1\right]}{u\sqrt{s}} \\ & I_1(2\sqrt{\beta us}) du ds - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\text{Pr}}} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{b\text{Pr}}} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] \\ & + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \text{Pr}}{2}\right) \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\text{Pr}}\tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \text{Pr}}{4\tau}} \right] + \frac{a}{b^2} \text{erf} c\left(\frac{\xi\sqrt{\text{Pr}}}{2\sqrt{\tau}}\right). \end{aligned} \quad (22)$$

$$v_{cs}(\zeta, \tau) = H(\tau) e^{-m\zeta} \cos(\omega\tau - n\zeta), \quad (25)$$

$$v_{ss}(\zeta, \tau) = e^{-m\zeta} \sin(\omega\tau - n\zeta), \quad (26)$$

which are periodic in time and independent of the initial condition. The transient solutions in equivalent but more suitable forms are written as

solutions (27) and (28) contain the thermal effects due to the presence of free convection term. Therefore, these transient solutions can be written as a sum of the mechanical $v_{ctme}(\zeta, \tau)$ and thermal $v_{ctth}(\zeta, \tau)$ components as below

$$v_{ct}(\zeta, \tau) = v_{ctme}(\zeta, \tau) + v_{ctth}(\zeta, \tau), \quad (30)$$

$$v_{st}(\zeta, \tau) = v_{stime}(\zeta, \tau) + v_{stth}(\zeta, \tau), \quad (31)$$

$$\begin{aligned} v_{ct}(\zeta, \tau) = & -\frac{H(\tau)\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds + \frac{a \exp\left(-\frac{\xi}{\sqrt{\alpha}}\right) (e^{b\tau} - b\tau - 1)}{b^2} \\ & + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \frac{\xi^2}{4s^2}\right) ds + \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \left(\frac{b}{\beta+b}\right) \frac{\xi^2}{4s^2}\right) ds \\ & + \frac{a\xi\sqrt{\beta}}{2b\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sqrt{s} \cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u} I_1(2\sqrt{\beta us}) du ds - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) \right. \\ & \left. + e^{\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \operatorname{Pr}}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\operatorname{Pr}} \tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \operatorname{Pr}}{4\tau}} \right], \end{aligned} \quad (27)$$

$$\begin{aligned} v_{st}(\zeta, \tau) = & -\frac{\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds - \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \frac{\xi^2}{4s^2}\right) ds \\ & + \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \left(\frac{b}{\beta+b}\right) \frac{\xi^2}{4s^2}\right) ds + \frac{a\xi\sqrt{\beta}}{2b\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sqrt{s} \sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u\sqrt{s}} \\ & I_1(2\sqrt{\beta us}) du ds - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] \\ & + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \operatorname{Pr}}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\operatorname{Pr}} \tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \operatorname{Pr}}{4\tau}} \right] + \frac{a \exp\left(-\frac{\xi}{\sqrt{\alpha}}\right) (e^{b\tau} - b\tau - 1)}{b^2} + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right), \end{aligned} \quad (28)$$

where

in which

$$\begin{aligned} m^2 &= \frac{\omega}{2[1+(\alpha\omega)^2]} \left[\sqrt{1+(\alpha\omega)^2} + \alpha\omega \right] \text{ and} \\ n^2 &= \frac{\omega}{2[1+(\alpha\omega)^2]} \left[\sqrt{1+(\alpha\omega)^2} - \alpha\omega \right]. \end{aligned}$$

The inverse Laplace transform of Eq. (14) gives the required temperature as

$$\theta(\zeta, \tau) = \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right). \quad (29)$$

It is important to note that the steady state solutions (25) and (26) are independent of thermal effects whereas, the transient

$$\begin{aligned} v_{ctme}(\zeta, \tau) &= -\frac{H(\tau)\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \\ & \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \end{aligned} \quad (32)$$

$$\begin{aligned} v_{stime}(\zeta, \tau) &= -\frac{H(\tau)\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \\ & \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4xu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \end{aligned} \quad (33)$$

$$\begin{aligned}
v_{ctth}(\xi, \tau) = & \frac{a \exp\left(-\frac{\xi}{\sqrt{\alpha}}\right)(e^{b\tau} - b\tau - 1)}{b^2} + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \frac{\xi^2}{4s^2}\right) ds \\
& + \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \left(\frac{b}{\beta+b}\right) \frac{\xi^2}{4s^2}\right) ds \\
& + \frac{a\xi\sqrt{\beta}}{2b\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sqrt{s} \cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u} I_1(2\sqrt{\beta us}) du ds \\
& - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] \\
& + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \operatorname{Pr}}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\operatorname{Pr}} \tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \operatorname{Pr}}{4\tau}} \right],
\end{aligned} \tag{34}$$

$$\begin{aligned}
v_{stth}(\xi, \tau) = & \frac{a \exp\left(-\frac{\xi}{\sqrt{\alpha}}\right)(e^{b\tau} - b\tau - 1)}{b^2} + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \frac{\xi^2}{4s^2}\right) ds \\
& + \frac{2a}{\sqrt{\alpha\pi}} \left(\frac{e^{b\tau}}{b^2} - \frac{\tau}{b} - \frac{1}{b^2}\right) \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \exp\left(-\frac{s^2}{\alpha} - \left(\frac{b}{\beta+b}\right) \frac{\xi^2}{4s^2}\right) ds \\
& + \frac{a\xi\sqrt{\beta}}{2b\sqrt{\alpha\pi}} \int_{\frac{\xi}{2\sqrt{\tau}}}^{\infty} \int_0^{\infty} \frac{\sqrt{s} \sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u} I_1(2\sqrt{\beta us}) du ds \\
& - \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{b\operatorname{Pr}}} \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] + \frac{a}{b} \left[\left(\tau + \frac{\xi^2 \operatorname{Pr}}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{\operatorname{Pr}}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{\operatorname{Pr}} \tau}{\sqrt{\pi}} e^{-\frac{\xi^2 \operatorname{Pr}}{4\tau}} \right],
\end{aligned} \tag{35}$$

in which the subscripts *me* and *th* are used for the mechanical and thermal parts of transient velocity.

Further, it is worth mentioning to note that solutions (21) and (22) are valid only for $\operatorname{Pr} \neq 1$, however to make these solutions valid for $\operatorname{Pr} = 1$, we once again derive our solutions by putting $\operatorname{Pr} = 1$ into Eq. (14) and using it in the transform solution of Eq. (9), the starting solutions are

corresponding to the cosine and sine oscillations of the plate and $a_1 = \frac{Gr}{\alpha}$. Now by employing the previous methodology, the starting solutions (36) and (37) can also be written as a sum of the steady-state and transient solutions.

$$\begin{aligned}
v_c(\xi, \tau) = & H(\tau) \exp(-m\xi) \cos(\omega\tau - n\xi) - \frac{a_1}{2} \left(\frac{\xi^4}{12} + \xi^2\tau + \tau^2\right) \operatorname{erf} c\left(\frac{\xi}{2\sqrt{\tau}}\right) \\
& - \frac{H(\tau)\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^{\tau} \int_0^{\infty} \frac{\cos(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\
& + \frac{a_1\xi\sqrt{\beta}}{4\sqrt{\alpha\pi}} \int_0^{\tau} \int_0^{\infty} \frac{(\tau-s)^2 \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\
& - \frac{a_1\xi}{12} \sqrt{\frac{\tau}{\pi}} \left(\frac{\xi^2}{2} + 5\tau\right) e^{-\frac{\xi^2}{4\tau}} + \frac{a_1\tau^2 e^{-\frac{\xi^2}{4\tau}}}{2},
\end{aligned} \tag{36}$$

$$\begin{aligned}
v_s(\xi, \tau) = & \exp(-m\xi) \sin(\omega\tau - n\xi) - \frac{a_1}{2} \left(\frac{\xi^4}{12} + \xi^2\tau + \tau^2\right) \operatorname{erf} c\left(\frac{\xi}{2\sqrt{\tau}}\right) \\
& - \frac{\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^{\tau} \int_0^{\infty} \frac{\sin(\omega\tau - \omega s) \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\
& + \frac{a_1\xi\sqrt{\beta}}{4\sqrt{\alpha\pi}} \int_0^{\tau} \int_0^{\infty} \frac{(\tau-s)^2 \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds \\
& - \frac{a_1\xi}{12} \sqrt{\frac{\tau}{\pi}} \left(\frac{\xi^2}{2} + 5\tau\right) e^{-\frac{\xi^2}{4\tau}} + \frac{a_1\tau^2 e^{-\frac{\xi^2}{4\tau}}}{2},
\end{aligned} \tag{37}$$

Limiting Cases

Equations (21) and (22) investigate the exact solutions for the starting motion of a second grade fluid for the cosine and sine oscillations of an isothermal vertical plate respectively and Eq. (28) represents the corresponding solution for temperature of the fluid. Since the present solutions are more general and the existing published results from the literature appear as special cases by taking suitable parameters such as Grashof number Gr , frequency of oscillations ω and the second grade parameter α equal to zero.

Case-I: Solutions in the Absence of Thermal Effects

In the absence of free convection, the solution of temperature (29), is unaffected by the thermal effects due to the reason that the free convection term Gr is not involved there, however by taking $Gr=0$ implies that $a=0$, Eqs. (21) and (22) yield Eqs. (38) and (39) as follows

$$v_c(\xi, \tau) = H(\tau) \exp(-m\xi) \cos(\omega\tau - n\xi) - \frac{H(\tau)\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \cos(\omega\tau - \omega s) \times \frac{1}{u\sqrt{s}} \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right) I_1(2\sqrt{\beta us}) du ds. \quad (38)$$

$$v_c(\xi, \tau) = \frac{\xi H(\tau)}{2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{\xi H(\tau)\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds + \frac{a\xi(e^{b\tau} - b\tau - 1)}{2b^2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{a\xi\sqrt{\beta}e^{b\tau}}{2b^2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\left[\exp\left(-\frac{\xi^2}{4zu} - u - \beta s - bs\right) - b(\tau - s) - 1\right]}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds + \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{bPr}} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{bPr}} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] - \frac{a}{b} \left[\left(\tau + \frac{\xi^2 Pr}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{Pr}\tau}{\sqrt{\pi}} e^{-\frac{\xi^2 Pr}{4\tau}} \right] + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}}\right). \quad (42)$$

$$v_s(\xi, \tau) = \exp(-m\xi) \sin(\omega\tau - n\xi) - \frac{\xi\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \sin(\omega\tau - \omega s) \times \frac{1}{u\sqrt{s}} \exp\left(-\frac{\xi^2}{4zu} - u - \beta s\right) I_1(2\sqrt{\beta us}) du ds, \quad (39)$$

which are identical to the starting solutions obtained by Nazar et al. (Eqs. (13) and (14) in [26]) describe the motion of the fluid for small and large times. Furthermore, for $\alpha \rightarrow 0$, $m=n=\sqrt{\frac{\omega}{2}}$, the steady parts of Eqs. (38) and (39) give the well known results

$$u_{cs}(y, t) = H(t) e^{-\sqrt{\frac{\omega}{2}}y} \cos\left(\omega t - \sqrt{\frac{\omega}{2}}y\right), \quad (40)$$

$$u_{ss}(y, t) = e^{-\sqrt{\frac{\omega}{2}}y} \sin\left(\omega t - \sqrt{\frac{\omega}{2}}y\right), \quad (41)$$

which are quite identical to the published results obtained by Erdogan (Eqs. (12) and (17) in [46]) and Feteca et al. (Eq. (17) in [47]).

Case-II: Solutions in the Absence of Oscillating Effects

Now let us assume that the infinite plate is set into impulsive motion after time $t=0^+$. The thermal component of velocity $v_{cth}(\xi, \tau)$ remain unchanged while the mechanical part of velocity $v_{cme}(\xi, \tau)$ is effected due to the frequency of oscillations ω . So, by taking $\omega \rightarrow 0$ into Eq. (21), the solution corresponding to the case when the plate applies impulsive motion to the fluid is given by

Case-III: Solutions in the Absence of Mechanical Effects

Here we assume that the infinite plate is kept at rest all the time. In this case the motion in the fluid together with heat transfer are only caused due to the presence of free convection because there is no disturbance from the bounding plate. Thus, the mechanical component of velocity is identically zero and consequently the velocity of the fluid $v(\xi, \tau)$ reduces to the thermal component

$$v_s(\xi, \tau) = \frac{a\xi(e^{b\tau} - b\tau - 1)}{2b^2\sqrt{\alpha\pi}} \int_0^\infty \frac{\exp\left(-\frac{\xi^2}{4zu} - u\right)}{u\sqrt{u}} du + \frac{a\xi\sqrt{\beta}e^{b\tau}}{2b^2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\left[\exp\left(-\frac{\xi^2}{4zu} - u - \beta s - bs\right) - b(\tau - s) - 1\right]}{u\sqrt{s}} I_1(2\sqrt{\beta us}) du ds + \frac{ae^{b\tau}}{2b^2} \left[e^{-\xi\sqrt{bPr}} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}} - \sqrt{b\tau}\right) + e^{\xi\sqrt{bPr}} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}} + \sqrt{b\tau}\right) \right] - \frac{a}{b} \left[\left(\tau + \frac{\xi^2 Pr}{2}\right) \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}}\right) - \frac{\xi\sqrt{Pr}\tau}{\sqrt{\pi}} e^{-\frac{\xi^2 Pr}{4\tau}} \right] + \frac{a}{b^2} \operatorname{erf} c\left(\frac{\xi\sqrt{Pr}}{2\sqrt{\tau}}\right). \quad (43)$$

We note that the solutions obtained as limiting cases (Case-II & Case-III) are also new and not available in the literature.

Skin-Friction

The expression for dimensional skin friction in case of a second grade fluid is given as

$$\tau_0^* = \left[\mu \frac{\partial u}{\partial y} + \alpha_1 \frac{\partial^2 u}{\partial y \partial t} \right]_{y=0}. \quad (44)$$

In dimensionless form Eq. (44) is written as

$$\tau_0 = \left[\frac{\partial v}{\partial \xi} + \alpha \frac{\partial^2 v}{\partial \xi \partial \tau} \right]_{\xi=0}, \quad (45)$$

where $\tau_0 = \frac{\tau_0^*}{\rho U^2}$.

Finally, Eq. (45) in view of Eq. (21) gives

$$\begin{aligned} \tau_0 = & -m \cos(\omega\tau) + n \sin(\omega\tau) + \alpha m \omega \cos(\omega\tau) + \alpha m \omega \sin(\omega\tau) \\ & - \frac{\sqrt{\beta}}{2\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{\cos(\omega\tau - \omega s) \exp(-u - \beta s)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) ds du \\ & + \frac{a\sqrt{\beta}}{2b\sqrt{\alpha\pi}} \int_0^\tau \int_0^\infty \frac{s \exp(-u - \beta s)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) ds du \\ & + \frac{\omega\sqrt{\alpha}\sqrt{\beta}}{2\sqrt{\pi}} \int_0^\tau \int_0^\infty \frac{\sin(\omega\tau - \omega s) \exp(-u - \beta s)}{u\sqrt{s}} I_1(2\sqrt{\beta us}) ds du \\ & - a \left(\frac{e^{b\tau} - b\tau - 1}{b^2\sqrt{\alpha}} \right) + a \left(\frac{-2b\sqrt{\text{Pr}}\tau + e^{b\tau}\sqrt{\pi}\sqrt{b\text{Pr}} \operatorname{erf}[\sqrt{b\tau}]}{b^2\sqrt{\pi}} \right) \\ & + a\alpha \left(\frac{-2b\sqrt{\text{Pr}}\tau + 2\sqrt{b\text{Pr}}\sqrt{b\tau} + 2\tau b e^{b\tau}\sqrt{\pi}\sqrt{b\text{Pr}} \operatorname{erf}[\sqrt{b\tau}]}{2\tau b^2\sqrt{\alpha}} \right) \\ & - a \left(\frac{\sqrt{\alpha}(be^{b\tau} - b\tau)}{b^2} \right), \end{aligned} \quad (46)$$

Nusselt Number

The rate of heat transfer evaluated from Eq. (29) is given by

$$\text{Nu} = \frac{\sqrt{\text{Pr}}}{\sqrt{\pi\tau}}. \quad (47)$$

Results and Discussion

A numerical assessment for the exact solutions (21) of the present problem corresponding to the cosine oscillations of the plate and (29) is performed. Using a computational software Mathcad, the results are plotted to illustrate the interesting features of the involved parameters on the starting solution corresponding to the cosine oscillations of the plate (Figs. 2–6) and temperature profiles (Fig. 6 and 7) whereas Figs. 8 and 9 are shown for the starting and steady-state velocities corresponding to the cosine and sine oscillations of the plate. In addition Fig. 10 is prepared to show the comparison of the present results with Nazar et al.

[26]. The parameters entering into the problem are second grade parameter α , Prandtl number Pr , thermal Grashof number Gr , dimensionless time τ , and phase angle $\omega\tau$.

Figure 2 shows the influence of α on the velocity field $v(\xi, \tau)$. It is clear from this figure that an increase in α results a decrease in the velocity. Physically, it is true because the higher values of α , are having greater stability than the smaller values. This behavior of α is quite similar to that of Sivaraj and Kumar (see Fig. 4 in [32]). Unlike [34,35], the effect of Prandtl number Pr for four different values as $\text{Pr} = 0.71, 0.9, 1.5$ and 7 upon velocity $v(\xi, \tau)$ is elucidated from Fig. 3. It is seen from this figure. 3 that in the case of heating of the plate or cooling of the fluid ($Gr < 0$), velocity $v(\xi, \tau)$ decreases when Prandtl number Pr increases. Physically, it is true as the Prandtl number describes the ratio between momentum diffusivity and thermal diffusivity and hence controls the relative thickness of the momentum and thermal boundary layers. As Pr increases the viscous forces (momentum diffusivity) dominate the thermal diffusivity and consequently decreases the velocity. The influence of thermal Grashof number Gr on velocity distribution $v(\xi, \tau)$ is elucidated from Fig. 4. It is clear from this figure that in the absence of thermal effect ($Gr = 0$) when the effect

of buoyant forces is negligible and the viscous forces are dominant, the velocity tends to steady-state faster than for the values of $Gr > 0$. It can be observed that velocity increases for the increasing values of Gr . It is also true physically as the Grashof number Gr describes the ratio of buoyancy forces to viscous forces. Therefore, an increase in the values of Gr leads to increase in buoyancy forces, consequently velocity increases.

The effect of dimensionless time τ on velocity $v(\xi, \tau)$ is illustrated from Fig. 5. It can be seen from this figure that velocity is a decreasing function of τ . The effect of phase angle $\omega\tau$ upon velocity $v(\xi, \tau)$ is elucidated from Fig. 6. It is observed that velocity $v(\xi, \tau)$ is fluctuating between -1 and 1 , tending to zero for large values of independent variable y . It is clear from this figure that the obtained solution (21) satisfies the corresponding boundary conditions given in Eq. (11). Hence this provides a useful mathematical check. The influence of Prandtl number Pr on temperature profile $\theta(\xi, \tau)$ is shown in Fig. 7. Four different values of $\text{Pr} = 0.015, 0.71, 1$ and 7 are chosen. They physically correspond to mercury, electrolyte, air and water respectively. It is found that temperature decreases when Pr is increased. As Pr is the ratio of momentum diffusivity (kinematic viscosity) to that of

Figure 2. Velocity profiles for different values of α when $Pr=0.71$, $Gr=0.5$, $\omega=2$, $\omega\tau=\frac{\pi}{3}$, and $\tau=1$.
doi:10.1371/journal.pone.0085099.g002

Figure 3. Velocity profiles for different values of Pr when $\alpha=0.2$, $Gr=-0.2$, $\omega=5$, $\omega\tau=\frac{\pi}{4}$, and $\tau=1$.
doi:10.1371/journal.pone.0085099.g003

Figure 4. Velocity profiles for different values of Gr when $\alpha=0.8$, $Pr=0.71$, $\omega=0.5$, $\omega\tau=\frac{\pi}{3}$, and $\tau=1$.
doi:10.1371/journal.pone.0085099.g004

thermal diffusivity, so the increase in Pr is actually increase in viscous forces (viscosity) which results a decrease in temperature profile. The effect of dimensionless time τ on the temperature

profiles $\theta(\xi, \tau)$ is shown in Fig.8. It can be seen from the figure that the effect of time τ on temperature $\theta(\xi, \tau)$ is quite opposite to the Prandtl number Pr as observed in Fig. 7.

Figure 5. Velocity profiles for different values of τ when $Pr=0.71$, $\alpha=0.2$, $Gr=0.5$, $\omega=2$ and $\omega\tau=\frac{\pi}{3}$.
doi:10.1371/journal.pone.0085099.g005

Figure 6. Velocity profiles for different values of $\omega\tau$ when $Pr=0.71$, $\alpha=0.2$, $Gr=0.5$, $\omega=1$ and $\tau=1$.
doi:10.1371/journal.pone.0085099.g006

A very important problem regarding the technical applicability of the starting solutions is to find the approximate time after which the fluid is moving according to the steady-state solutions. More exactly, in practice it is necessary to know the required time to attain the steady state [26]. For this purpose, the variations of the corresponding starting and steady-state velocities with the distance from the wall are depicted in Figs. 9 and 10. At small values of time, the difference between unsteady and steady-state velocities is large enough. This difference rapidly decreases and it can be clearly seen from the figures that the required time ($\tau=6$) to reach the steady-state for the cosine oscillations of the boundary is

smaller than that for the sine oscillations ($\tau=10$). A comparative study of the present solution (21) corresponding to the cosine oscillations of the plate is provided in Fig. 11 with published results of Nazar et al. (Eq. (13) in [26]). It is found that in the absence of free convection ($Gr=0$) the present results are identical with those of Nazar et al. [26].

The numerical results for skin friction τ_0 are shown in Table 1 for various embedded parameters. It is found that the skin friction decreases when α is increased. On the other hand, the influence of Prandtl number Pr on skin friction shows that τ_0 decreases when Pr increases whereas it increases for large

Figure 7. Temperature profiles for different values of Pr when $\tau=1$.
doi:10.1371/journal.pone.0085099.g007

Figure 8. Temperature profiles for different values of τ when $Pr=0.71$.

doi:10.1371/journal.pone.0085099.g008

Figure 9. Variations of the starting and steady-state solutions with the distance from the wall, for the cosine oscillations of the boundary, corresponding to relation (21) curves $v_{1s}(\xi, \tau)$, $v_{2s}(\xi, \tau)$ and relation (25) curves $v_{1ss}(\xi, \tau)$, $v_{2ss}(\xi, \tau)$, when $Gr=0$, $\omega=0.5$ and $\alpha=0.8$.

doi:10.1371/journal.pone.0085099.g009

Figure 10. Variations of the starting and steady-state solutions with the distance from the wall, for the sine oscillations of the boundary, corresponding to relation (22) curves $v_{1s}(\xi, \tau)$, $v_{2s}(\xi, \tau)$ and relation (26) curves $v_{1ss}(\xi, \tau)$, $v_{2ss}(\xi, \tau)$, when $Gr=0$, $\omega=0.5$ and $\alpha=0.8$.

doi:10.1371/journal.pone.0085099.g010

values of Gr , τ and $\omega\tau$. The effects of Pr and τ on Nusselt number Nu are studied numerically in Table 2. It is found that Nu decreases when Pr increases. Physically this behavior is acceptable because when Pr increases, it decreases the resistance and consequently enhances the rate of heat transfer. The influence of τ on Nu is found quite opposite to that of Pr .

Conclusions

The heat transfer analysis of a second grade fluid for unsteady free convection flow past an isothermal vertical plate oscillating in its plane is investigated. Closed form solutions of the problem are obtained by using the Laplace transform technique. The starting solutions (21) and (22) are expressed in terms of steady-state and transient solutions. It is found that they satisfy the imposed initial and boundary conditions and can be easily reduced to the similar

Figure 11. Comparative study of the present solution (21) to those of Nazar et al. (Eq. (13) in [26]) corresponding to the cosine oscillations of the plate when $Gr=0$, $\omega=0.5$, $\alpha=0.8$ and $\omega\tau=\frac{\pi}{3}$.

doi:10.1371/journal.pone.0085099.g011

Table 1. Variation in skin-frictions τ_0

α	P_r	G_r	ω	τ	ωt	τ_0
0.2	0.71	0.5	0.5	1	$\pi/3$	7.137
0.2	0.71	0.5	0.5	1	$\pi/3$	2.150
0.2	0.9	1	0.5	1	$\pi/3$	14.728
0.4	0.71	0.5	0.5	1	$\pi/3$	1.203
0.2	0.71	0.5	0.8	1	$\pi/3$	7.194
0.2	0.71	0.5	0.5	2	$\pi/3$	32.00
0.2	0.71	0.5	0.5	2	π	9.199

doi:10.1371/journal.pone.0085099.t001

solutions in the literature by taking Grashof number Gr , frequency of oscillations ω and the second grade parameter α equal to zero. The effects of various parameters on velocity and temperature profiles are graphically studied whereas the results for skin-friction and Nusselt number are computed in tables. The following conclusions are extracted from this study.

- Increasing second grade parameter α decreases fluid velocity.
- Velocity for electrolyte solution is greater than air and water.
- The presence of free convection enhances the fluid motion.
- Temperature decreases for large values of Pr .
- The Nusselt number increases when Pr is increased
- The skin friction increases when both time τ and phase angle ωt are increased.

References

1. Erdogan ME, Imrak CE (2007) On some unsteady flows of a non-Newtonian fluids. *Appl Math Model* 31: 170–180.
2. Vieru D, Akhtar W, Fetecau C, Fetecau C (2007) Starting solutions for the oscillating motion of a Maxwell fluid in cylindrical domains. *Meccanica* 42: 573–583.
3. Fetecau C, Jamil M, Fetecau C, Siddique I (2009) A note on the second problem of Stokes for Maxwell fluids. *Int J Non-Linear Mech* 44: 1085–1090.
4. Fetecau C, Akhtar W, Imran MA, Vieru D (2010) On the oscillating motion of an Oldroyd-B fluid between two infinite circular cylinders. *Comput Math Appl* 59: 2836–2845.
5. Vieru D, Rauf A (2011) Stokes flows of a Maxwell fluid with wall slip condition. *Can J Phys* 89: 1–12.
6. Khan I, Fakhra K, Anwar MI (2012) Hydromagnetic rotating flows of an Oldroyd-B fluid in a porous medium. *Special Topics and Review in Porous Media* 3: 89–95.
7. Khan I, Fakhra K, Shafie S (2012) Magnetohydrodynamic rotating flow of a generalized Burgers' fluid in a porous medium with Hall current. *Trans Porous Media* 91: 49–58.
8. Vieru D, Zafar AA (2013) Some Couette flows of a Maxwell fluid with wall slip condition. *Appl Math Inf Sci* 7: 209–219.
9. Khan I, Farhad A, Sharidan S (2013) Stokes' second problem for magnetohydrodynamics flow in a Burgers' fluid: Cases $\gamma = \lambda^2/4$ and $\gamma > \lambda^2/4$. *PLOS ONE* 8(5): e61531.
10. Nandephanavar MM, Abel MS, Tawade J (2010) Heat transfer in a Walters Liquid B fluid over an impermeable stretching sheet with non-uniform heat source/sink and elastic deformation. *Commun Non-linear Sci Numer Simulat* 15: 1791–1802.
11. Ghasemi E, Bayat M, Bayat M (2011) Viscoelastic MHD flow of Walters liquid B fluid and heat transfer over a non-isothermal stretching sheet. *Int J Phys Sci* 6: 5022–5039.
12. Chang TB, Mehmood A, Beg OA, Narahari M, Islam MN, et al. (2011) Numerical study of transient free convective mass transfer in a Walters-B viscoelastic flow with wall suction. *Commun Non-linear Sci Numer Simulat* 16: 216–225.
13. Fosdick RL, Rajagopal KR (1979) Anomalous feature in the model of second-order fluids. *Arch Ratio Mech Anal* 70: 145–152.
14. Dunn JE, Fosdick RL (1974) Thermodynamics, stability and boundedness of fluids of complexity 2 and fluids of second-grade. *Arch Ratio Mech Anal* 56: 191–252.

Table 2. Variation in Nusselt number Nu .

P_r	τ	Nu
0.71	1	0.47
7	1	1.492
0.71	2	0.33

doi:10.1371/journal.pone.0085099.t002

- In the absence of free convection ($Gr = 0$) the present solutions are found identical to those obtained by Nazar et al. [26].

Supporting Information

Appendix S1 (PDF)

Acknowledgments

The authors would like to acknowledge the Research Management Centre – UTM for the financial support through vote numbers 4F109 and 04H27 for this research.

Author Contributions

Conceived and designed the experiments: FA IK SS. Performed the experiments: IK FA SS. Analyzed the data: FA IK SS. Contributed reagents/materials/analysis tools: IK FA SS. Wrote the paper: FA IK SS.

15. Rajagopal KR (1982) A note on unsteady unidirectional flows of a non-Newtonian fluid. *Int J Non-Linear Mech* 17: 369–373.
16. Hussain M, Hayat T, Asghar S, Fetecau C (2010) Oscillatory flows of second grade fluid in a porous space. *Nonlinear Anal Real World Appl* 11: 2403–2414.
17. Erdogan ME, Imrak CE (2005) An exact solution of the governing equation of a fluid of second-grade for three-dimensional vortex flow. *IJ Eng Sci* 43: 721–729.
18. Erdogan ME, Imrak CE (2005) On the comparison of two different solutions in the form of series of the governing equation of an unsteady flow of a second grade fluid. *Int J Non-Linear Mech* 40: 545–550.
19. Fetecau C, Fetecau C (2005) Starting solutions for some unsteady unidirectional flows of a second grade fluid. *Int J Eng Sci* 43: 781–789.
20. Asghar S, Nadeem S, Hanif K, Hayat T (2006) Analytic solution of stokes second problem for second-grade fluid. *Math Probl Eng* 2006: 1–9.
21. Tiwari AK, Ravi SK (2009) Analytical studies on transient rotating flow of a second grade fluid in a porous medium. *Adv Theor Appl Mech* 2: 33–41.
22. Fetecau C, Fetecau C (2005) Starting solutions for some unsteady unidirectional flows of a second grade fluid. *Int J Eng Sci* 43: 781–789.
23. Khan I, Ellahi R, Fetecau C (2008) Some MHD flows of a second grade fluid through the porous medium. *Journal Porous Media* 11: 389–400.
24. Fetecau C, Fetecau C (2006) Starting solutions for the motion of a second grade fluid due to longitudinal and torsional oscillations of a circular cylinder. *Int J Eng Sci* 44: 788–796.
25. Ali F, Khan I, Samiulhaq, Norzieha M, Sharidan S (2012) Unsteady magnetohydrodynamic oscillatory flow of viscoelastic fluids in a porous channel with heat and mass transfer. *J Phy Soc Japan* 81: 064402.
26. Nazar M, Fetecau C, Vieru D, Fetecau C (2010) New exact solutions corresponding to the second problem of Stokes for second grade fluids. *Nonlinear Anal Real World Appl* 11: 584–591.
27. Ali F, Norzieha M, Sharidan S, Khan I, Hayat T (2012) New exact solutions of Stokes' second problem for an MHD second grade fluid in a porous space. *Int J Non-Linear Mech* 47: 521–525.
28. Anwar I, Amin N, Pop I (2008) Mixed convection boundary layer flow of a viscoelastic fluid over a horizontal circular cylinder. *Int J Non-Linear Mech* 43: 814–821.
29. Damsch RA, Shatnawi AS, Chamkha AJ, Duwairi HM (2008) Transient mixed convection flow of a second-grade visco-elastic fluid over a vertical surface. *Nonlinear Anal Modell and Control* 13: 169–179.
30. Hsiao KL (2011) MHD mixed convection for viscoelastic fluid past a porous wedge. *Int J Non-Linear Mech* 46: 1–8.

31. Kavitha KR, Murthy CVR (2011) Mixed convection flow of a second grade fluid in an inclined porous channel. *Int J Phys Math Sci* 1: 120–139.
32. Sivaraj R, Kumar BR (2012) MHD mixed convective flow of viscoelastic and viscous fluids in a vertical porous channel. *Applications Appl Math* 7: 99–116.
33. Mishra SR, Dash GC, Acharya M (2013) Mass and heat transfer effect on MHD flow of a visco-elastic fluid through porous medium with oscillatory suction and heat source. *Int J Heat and Mass Transf* 57: 433–438.
34. Pop I, Watanabe T (1992) Free convection with uniform suction or injection from a vertical cone for constant wall heat flux. *Int Comms in Heat and Mass Transfer* 19: 275–283.
35. Kafousias NG (1992) MHD free convection flow through a nonhomogeneous porous medium over an isothermal cone surface. *Mech Res Commun* 19: 89–94.
36. Gebhart B, Jaluria y, Mahajan RL, Sammakia B (1988) Buoyancy induced flows and transport. Hemisphere publishing corporation New York.
37. Sparrow EM, Greg JL (1958) The variable fluid property problem in free convection. *ASME* 80: 869–876.
38. Minkowycz WJ, Sparrow EM (1967) Free convection heat transfer to stream under variable property condition. *Int J Heat Mass Transfer* 9: 1145–1147.
39. Carey VP, Mollendorf (1980) Variable viscosity effects in several natural convection flows. *Int J Heat and Mass Transfer* 23: 95–109.
40. Rup K (1988) Transient Natural convection heat transfer in non-Newtonian second order fluids. *J Theoretical App Mech* 1: 34.
41. Jang JY, Lin CN (1988) Free convection flow over an uniform-heat-flux surface with temperature-dependent viscosity. *W/irme- und Stoffübertragung* 23: 213–217.
42. Lai FC, Kulacki FA (1990) The effect of variable viscosity on convective heat transfer along a vertical surface in a saturated porous medium. *Int J Heat Mass Transfer* 33: 1028–1031.
43. Hsu SH, Jamieson AM (1993) Viscoelastic behaviour at the thermal sol-gel transition of gelatin. *Polymer* 34: 2602–2608.
44. Bandelli R (1995) Unsteady unidirectional flows of second grade fluids in domains with heated boundaries. *Int J Non-linear Mech* 30: 263–269.
45. Damsch RA, Shatnawi AS, Chamkha AJ, Duwairi HM (2008) Transient mixed convection flow of a second grade viscoelastic fluid over a vertical surface. *Nonlinear Analysis: Modelling and Control* 13: 169–179.
46. Erdogan ME (2000) A note on unsteady flow of a viscous fluid due to an oscillating plane wall. *Int J Non-Linear Mech* 35: 1–6.
47. Fetecau C, Vieru D, Fetecau C (2007) A note on second problem of Stokes for Newtonian fluids. *Int J Non-Linear Mech* 43: 451–457.